



Confined Space

CONFINED SPACE



9543



9543-15

Ships Direct FOB Mfg.



12" Plastic Axial Blower with Canister and Ducting

- » UV-, corrosion- and chemical-resistant polyethylene in "safety orange"
- » Canister attaches to intake or output of blower for suction or ventilation
- » Molded carry handle
- » 1 HP, 115/230V, 50/60Hz, 11A, 3400 RPM

Flow rates*:

- Free air: 1842 CFM
- One 90° bend: 1004 CFM
- Two 90° bends: 933 CFM
- » Certifications: UL Listed, CSA Certified Standard C22.2 No.113, CE Certified

ITEM #	ORDER #	DESCRIPTION	UOM
9543	33429543	Blower Only	EA
9543-15	33429544	Blower with Canister and 15' Ducting	EA
9543-25	33429545	Blower with Canister and 25' Ducting	EA



16" Plastic Axial Blower with Canister and Ducting

- » UV-, corrosion- and chemical-resistant polyethylene in "safety orange"
- » Canister attaches to intake or output of blower for suction or ventilation
- » Molded carry handle
- » 1 HP, 115V/60Hz, 9A, 3450 RPM

Flow rates*:

- Free air: 3200 CFM
- One 90° bend: 2350 CFM
- Two 90° bends: 2250 CFM
- » Certifications: UL Listed, CSA Certified Standard C22.2 No.113

Ships Direct FOB Mfg.



9553



9553-15

ITEM #	ORDER #	DESCRIPTION	UOM
9553	334205841	Blower Only	EA
9553-15	334205851	Blower with Canister and 15' Ducting	EA
9553-25	334205861	Blower with Canister and 25' Ducting	EA



16" Ventilation Axial Blower

- » Complete unit epoxy powder coated in "safety orange"
- » Interchangeable flange for intake/exhaust side mounting
- » 18-gauge cold rolled steel housing
- » Integrated carrying handles
- » Equipped with four rubber feet
- » Certifications: CSA Certified Standard C22.2 No.113, UL Listed

Ships Direct FOB Mfg.



9515



9515-01

ITEM #	ORDER #	DESCRIPTION	MOTOR	FREE AIR*	ONE 90** BEND	TWO 90** BENDS	UOM
9515	334203291	Standard Blower	1/2 HP, 115V/60Hz, 7.2A, 1725 RPM	3400 CFM	2800 CFM	2300 CFM	EA
9516	334203321	High Output Blower	2 HP, 115/230V, 60Hz, 21/10.5A, 3450 RPM	5500 CFM	4950 CFM	4400 CFM	EA
9515-01	334203311	Explosion-Proof Blower	1/2 HP, 115/230V, 60Hz, 8.2/4.1A, 1725 RPM	2900 CFM	1800 CFM	1750 CFM	EA

Confined Space



20" Ventilation Axial Blower

- » Complete unit epoxy powder coated in "safety orange"
- » Interchangeable flange for intake/exhaust side mounting
- » 16-gauge cold rolled steel housing
- » Integrated carrying handles
- » Equipped with four rubber feet
- » Certifications: CSA Certified Standard C22.2 No.113, UL Listed

Ships Direct FOB Mfg.



ITEM #	ORDER #	DESCRIPTION	MOTOR	FREE AIR*	ONE 90** BEND	TWO 90** BENDS	UOM
9525	33429525	Standard Blower	1/2 HP, 115V/60Hz, 7.2A, 1725 RPM	4650 CFM	3150 CFM	2950 CFM	EA
9525-50	33422550	High Output Blower	2 HP, 115/230V, 60Hz, 21/10.5A, 3450 RPM	7500 CFM	6700 CFM	6130 CFM	EA
9525-01	33422501	Explosion-Proof Blower	1/2 HP, 115/230V, 60Hz, 8.2/4.1A, 1725 RPM	4650 CFM	3150 CFM	2950 CFM	EA



8" Plastic COM-PAX-IAL Blowers

- » 9533-15 and 9533-25 models are the lightest and smallest in the industry
- » UV-, corrosion- and chemical-resistant polyethylene in "safety orange"
- » Bottom enclosure to protect electrical component
- » Carry handle molded into blower and canister housing
- » Steel powder coated grill
- » Certifications - CE Certified, CSA Certified Standard C22.2 No.113, UL Listed



Ships Direct FOB Mfg.

ITEM #	ORDER #	DESCRIPTION	FREE AIR*	ONE 90** BEND	TWO 90** BENDS	UOM
1/3 HP, 115/230V, 50/60Hz, 4.8/2.4A, 3400 RPM						
9533	334203461	AC Blower Only	831 CFM	709 CFM	586 CFM	EA
9533-15	334203481	AC Blower with Canister and 15' Ducting	831 CFM	709 CFM	586 CFM	EA
9533-25	334203491	AC Blower with Canister and 25' Ducting	831 CFM	709 CFM	586 CFM	EA
1/4 HP, 12V DC, 2.2A, 3800 RPM						
9536	334203561	DC Blower Only	816 CFM	526 CFM	442 CFM	EA
9536-15	334203571	DC Blower with Canister and 15' Ducting	816 CFM	526 CFM	442 CFM	EA
9536-25	334203581	DC Blower with Canister and 25' Ducting	816 CFM	526 CFM	442 CFM	EA
1/3 HP, 115/60Hz, 2.2A, 3250 RPM						
9538	334295381	Explosion Proof Blower Only	900 CFM	650 CFM	625 CFM	EA
9538-15	33423815	Explosion Proof Blower with Canister and 15' Ducting	900 CFM	650 CFM	625 CFM	EA
9538-25	33423825	Explosion Proof Blower with Canister and 25' Ducting	900 CFM	650 CFM	625 CFM	EA



8" Axial Blowers with Canister and Ducting

- » Design allows ducting to collapse into a built-in canister
- » Unit can be stored vertically
- » 1/3 HP, 120V/60Hz, 3A, 3200 RPM
- » 18-gauge cold rolled steel housing
- » 14-gauge steel enclosed panel to protect electrical components

Flow rates*:

- Free air: 1275 CFM
- One 90° bend: 661 CFM
- Two 90° bends: 582 CFM
- » Certified to CSA STD C22.2 No 113, UL Listed
- » Air delivery certified CEESI

Ships Direct FOB Mfg.



ITEM #	ORDER #	DESCRIPTION	UOM
9514	334203231	Includes 15' Ducting	EA
9514-25	334203271	Includes 25' Ducting	EA



Confined Space



Air Bag Blowers with Ducting

- » Blower system with ducting built into heavy duty bag
- » Carry handle with molded-in 2-speed switch
- » Steel/powder coated housing and grills
- » Unique bag with openings for plug/cord, inlet and outlet
- » 15' duct mounted on the blower and stored inside bag
- » Both carrying handle and shoulder strap allows for easy transportation

Ships Direct FOB Mfg.



9535-08

ITEM #	ORDER #	DESCRIPTION	MOTOR	FREE AIR*	UOM
9535-08	334205381	8" System	1/4 HP, 120V/60Hz, 1.4A, 3300 RPM	760 CFM	EA
9535-12	334235121	12" System	1/2 HP, 120V/60Hz, 3.8A, 3300 RPM	1840 CFM	EA



9401-25



Ships Direct FOB Mfg.

Magnetic Manhole Lid Lifters

- » Lift heavy manhole lids alone
- » Clamps to cover without any special tools
- » Eliminates the use of pry bars
- » For safety must be in contact with the cover to be engaged
- » Collapsible for easy storage and transportation

ITEM #	ORDER #	DESCRIPTION	UOM
9401-25	33422127	Steel Dolly and Magnet (Lift Weight: 660 lbs. Flat Items, 330 lbs. Round Items)	EA
9401-25A	33422129	Aluminum Dolly and HD Magnet (Lift Weight: 660 lbs. Flat Items, 330 lbs. Round Items)	EA
9401-26A	33422130	Aluminum Dolly and HD Magnet (Lift Weight: 900 lbs. Flat Items, 450 lbs. Round Items)	EA



9401-20



Manhole Accessories

Ships Direct FOB Mfg.

Guard Rail

- » Designed to protect an area of 33"L x 33"W
- » Support arm gives guardrail added support
- » Two chains with hook for additional security
- » 2 welded marker flags
- » Simple one-piece construction assembles without tools
- » Collapses to 44"L x 32"W x 4"H for compact storage

High Impact Manhole Shield

- » Bright yellow material that resists fading
- » Fits 28", 30" and 32" diameter manholes
- » Inflatable watertight seal
- » 4-outrigger support gussets that stabilize the shield
- » 12" tall to keep water and mud out of manhole

Hook Manhole Lifter

- » 21" heat treated, cadmium-plated all steel alloy hook
- » Lockable hook for convenient storage
- » Rubber grip on handle, rubber foot to minimize slippage
- » Support leg angled 6" for leverage



9401

9401-12

ITEM #	ORDER #	DESCRIPTION	UOM
9401	334202661	Guard Rail	EA
9401-12	334202681	Plastic Shield	EA
9401-20	334202691	Steel, Hook Lifter	EA